



???????? :: ??? ?? ??? ??

??? ?????? :: TS-855eU

???? ???????? :: 10

?????: 8.10kg

???????88.60mm x 432.00mm x 297.40mm

???? ??????:

## ????? ????????

| ????? ????????????        | Intel ® Atom® C5125 8-core processor, 2.8GHz                                                                   |
|---------------------------|----------------------------------------------------------------------------------------------------------------|
| ????? ????                | 64-bit x86                                                                                                     |
| ???????????               |                                                                                                                |
| ????? ????????            | ? (AES-NI)                                                                                                     |
| ????????                  | 8 GB non-ECC SODIMM DDR4 (1 x 8 GB)                                                                            |
| ??? ?????? ??????????     | 8                                                                                                              |
| ??? ?????????? ?????????? | 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives                 |
| ????? ?????? ??????????   | ? (Not supported M.2 SSD)                                                                                      |
| ????????                  |                                                                                                                |
| ????? USB ?????? 3.2      | 4                                                                                                              |
| ????? ????????            | 3 x 60mm, 12VDC                                                                                                |
| ????? ??????              | 250W PSU, 100 - 240V                                                                                           |
| ????????/???????          |                                                                                                                |
| Total Memory Slots        | 2 x SODIMM DDR4 Support ECC memory For dual-DIMM configuration, you must use a pair of identical DDR4 modules. |
| Maximum Memory Capacity   | 64 GB ( 2 x 32 GB)                                                                                             |
| M.2 Drive Slots           | 2 x M.2 2280 (PCIe Gen 3 x 4)                                                                                  |
| PCIe Expansion            | 2 x PCIe Gen3 (x4) Slot 1: PCIe Gen 3 (x4) Slot 2: PCIe Gen 3 (x4)                                             |
| Form Factor (RU)          | 2U Short Depth Rackmount                                                                                       |
| Floating Point Unit       | ?                                                                                                              |
| Flash Memory              | 5GB (Dual boot OS protection)                                                                                  |

|                                                                 |                                                  |
|-----------------------------------------------------------------|--------------------------------------------------|
| Wake on LAN (WOL)                                               | ?                                                |
| Jumbo Frame                                                     | ?                                                |
| HDMI™ Output                                                    | Optional via a PCIe graphics card                |
| LED Indicators                                                  | HDD 1-8, Status, LAN, USB, Power                 |
| Buttons                                                         | Power, Reset                                     |
| Operating Temperature                                           | 0 - 40 °C (32°F - 104°F)                         |
| Storage Temperature                                             | -20 - 70°C (-4°F - 158°F)                        |
| Relative Humidity                                               | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Consumption: Disk Standby Mode                            | 49.799                                           |
| System Warning                                                  | Buzzer                                           |
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 2500                                             |

????? ????????



