

# DiskStation DS1522+



**Brand:** Synology  
**Product Code:** DS1522+  
**Availability:** 10  
**Weight:** 2.70kg  
**Dimensions:** 223.00mm x 230.00mm x 166.00mm

**Price: 60,294.00EGP**

## Short Description

Synology 5 Bay DiskStation DS1522+

## Description

### Flexible data management for homes and small business

The 5-bay Synology DiskStation DS1522+ is easy to scale and expand as your needs change, with optional support for up to 15 drives, 10GbE networking, and NVMe SSD caching. Powered by Synology DiskStation Manager (DSM), it offers a flexible all-in-one solution for data sharing, synchronization, backup, and surveillance.




Over 736/796 MB/s sequential read/write<sup>1</sup>



8 GB DDR4 ECC (max. 32 GB)

Memory



Four built-in 1GbE ports with easy 10GbE option<sup>2</sup>

Connectivity



Up to 15 drive bays with 2 DX517 expansion units<sup>2</sup>

Scalability



A trademark of Ziff Davis, LLC. Used under license.

Reprinted with permission. © 2024 Ziff Davis, LLC. All Rights Reserved.

Synology has won the Readers' Choice & Business Choice for best NAS devices in 2024 from PCMag. This is the 13th consecutive year Synology has won the Readers' Choice award and 10th overall win for Business Choice award.

## **Simply faster**

DS1522+ can handle more demanding application workloads and a greater number of concurrent users compared to prior-generation systems. Experience faster file indexing in Synology Drive, photo organization in Photos, and concurrent file transfers.

Synology Drive

24%

faster file indexing

Synology Photos

25%

faster photo indexing

Multiple file transfers

32%  
faster random write

## **Flexible networking options**

Reduce transfer times with the DS1522+, designed to accelerate your workloads. Easily add faster networking and NVMe drives to further boost performance.

Up to 736/796 MB/s read/write

Up to 10GbE networking

2 x M.2 NVMe cache & storage pool

**Everything you need for your home office**

Make the most of high-performance networking and file access without taking up unnecessary space. DS1522+ comes equipped with 5 bays and can scale up to 15 bays with 2 DX517 expansion units as your data needs grow.

5 bays 80 TB



15 bays 240 TB

## **Store, share, and protect**

Manage all your documents, photos, and other files, back up applications and devices, or protect your assets with professional video surveillance.



**File Server**



**Multi-Layered Backup**



## Smart Surveillance

## **File Server**

Store and access files from all your devices, and protect them with smart versioning.  
Sort, manage, share, and sync your data across locations.

## **A private cloud for all your devices**

Store, sync, and access data from any device, wherever you are with Synology's private cloud solution. Sync data between different platforms and devices, and access your files through mobile apps, desktop clients, and a browser-based interface. Leverage smart versioning to back up important data via desktop and mobile applications.

## **Dependable and secure network storage**

Use shared folders on your Synology device as reliable storage available from anywhere on your local network over all common protocols (SMB/NFS/WebDAV/FTP). Protect your files against accidental changes and removal or even malware attacks with built-in snapshot technology and other backup options.



## **Sort, manage, and share your files**

Rely on our file, photo, and multimedia management apps to sort your data by metadata, filters, and labels. Safely share files and folders with family, colleagues, or business customers thanks to granular access and sharing permissions. Create convenient sharing links and secure shared files with expiration dates and individual passwords. Let friends or clients review photos remotely and give easy feedback through star ratings.



## **Sync files and folders between sites**

Benefit from two efficient ways to keep files and folders synchronized between different locations — such as your home and your business, or teams in different countries. Sync folders one or two-way between Synology devices using Synology Drive ShareSync, a free site-to-site solution. Or choose to leverage our secure data centers to store your data in the cloud, while keeping a cache of frequently accessed or manually pinned files on your DS1522+ with Synology Hybrid Share. Such hybrid cloud storage lets you access data at LAN speeds without being limited by your local storage size or bandwidth.

## **Multi-Layered Backup**

Back up files, folders, physical devices, VMs, and SaaS applications with free solutions, and protect your NAS with built-in technologies.

## **Protect full endpoints, servers, and VMs**

Securely back up Windows clients and servers, Linux endpoints, VMware® and Hyper-V® virtual machines, and other Synology devices. Leverage built-in deduplication technology to greatly reduce backup sizes and multi-versioning restore systems to a time point of your choice.

## **Make local backups of your cloud apps**

Protect business Microsoft 365 and Google Workspace accounts by maintaining complete offline copies of your crucial information and configurations with Active Backup for Microsoft 365 and Active Backup for Google Workspace.

## **Back up documents and multimedia**

Set up backup tasks to protect important folders on your PC and macOS device with Synology Drive. On your mobile device, automatically save another copy of the photos and videos you take, and easily organize and share them through Synology Photos.

## **Back up your NAS to multiple destinations**

Protecting the data on your Synology system, and your server itself, means storing frequent emergency copies to multiple locations. Built-in tools in Synology DSM let you efficiently back up files, folders, or your entire system from your device to remote servers, external drives, or Synology and third-party cloud storage, with space-saving deduplication technology reducing total backup sizes, and customizable backup and retention schedules for maximum flexibility.

## **High-frequency protection with snapshots**

Take point-in-time snapshots of shared folders and LUNs at intervals of down to 5 minutes to protect against data loss, accidental deletion, or malware attacks. Set a custom retention schedule and roll back files and VMs to a version that is unaffected.

## **Smart Surveillance**

Transform your Synology device into a full-featured video management system for a wide range of compatible IP cameras.

## **Wide compatibility**

Connect up to 40 IP cameras from a selection of over 8,300 validated models thanks to wide camera compatibility and ONVIF support in Synology Surveillance Station.

## **Secure and private**

Footage stored locally can be protected from unauthorized access by industry-standard AES-256 encryption.

## **24/7 everywhere access**

Monitor live streams or watch recordings from web browser, desktop client, or the DS cam mobile app.



**Software**

DSM Specifications

[Storage Management](#)

Maximum Single Volume Size	108 TB
Maximum Internal Volume Number	64
M.2 SSD Storage Pool Support*	
SSD Read/Write Cache	
<a href="#">(Determining cache size)</a>	
SSD TRIM	
Supported RAID Type	<ul style="list-style-type: none"><li>• Synology Hybrid RAID</li><li>• Basic</li><li>• JBOD</li><li>• RAID 0</li><li>• RAID 1</li><li>• RAID 5</li><li>• RAID 6</li><li>• RAID 10</li></ul>
RAID Migration	<ul style="list-style-type: none"><li>• Basic to RAID 1</li></ul>

Volume Expansion with  
Larger HDDs

- Basic to RAID 5
- RAID 1 to RAID 5
- RAID 5 to RAID 6
- Synology Hybrid RAID
- RAID 1
- RAID 5
- RAID 6
- RAID 10

Volume Expansion by  
Adding a HDD

- Synology Hybrid RAID
- JBOD
- RAID 5
- RAID 6

Global Hot Spare Supported  
RAID Type

- Synology Hybrid RAID
- RAID 1
- RAID 5
- RAID 6
- RAID 10

Notes

- Creating M.2 storage pools requires the use of Synology-verified SSDs, which are rigorously tested under extreme temperature conditions. Thermal parameters for SSDs and NAS units are fine-tuned to ensure optimal management of thermal conditions under I/O-intensive environments. ([Learn more](#))
- Usable capacity for each volume will be lower than the maximum volume size and is dependent on the filesystem and

the amount of system metadata stored.

- Actual maximum storage pool and volume sizes vary depending on drives used, the number of drive bays available, and the RAID configuration.
- Each internal volume (may consist of multiple drives) is expandable up to 108TB.

## File System

Internal Drives

- Btrfs
- ext4

External Drives

- Btrfs
- ext4
- ext3
- FAT
- NTFS
- HFS+
- exFAT

## File Services

File Protocol

- SMB
- AFP
- NFS
- FTP
- WebDAV
- Rsync

Maximum Concurrent 2,000

SMB/AFP/FTP Connections

Maximum Concurrent 2,000

SMB/AFP/FTP Connections

(with RAM expansion)

Windows Access Control

List (ACL) Integration

NFS Kerberos Authentication

Notes

- Regarding data concerning tests with RAM expansion, all memory slots are

installed with the maximum capacity of supported RAM.

- The testing standard was based on the maximum number of concurrent connections supported by this model. During the testing, 25% of the connections were used to transfer files concurrently. The transfer process guaranteed that the connections were not interrupted; the minimum transfer speed was not guaranteed.

#### [Account & Shared Folder](#)

Maximum Local User Accounts	2,048
Maximum Local Groups	256
Maximum Shared Folder	512
Maximum Shared Folder Sync Tasks	32

#### [Hybrid Share](#)

#### [Hyper Backup](#)

Hybrid Share Folder Number	10
Folder and Package Backup	
Entire System Backup	
Notes	Full-system backup requires DSM 7.2 or later.

#### [High Availability](#)

#### [Log Center](#)

#### Virtualization

Synology High Availability	
Syslog Events per Second	800
VMware ESXi 6.5 and VAAI	
Windows Server 2022	
Citrix Ready	
OpenStack	

#### [General Specifications](#)

Supported Protocols	SMB1 (CIFS), SMB2, SMB3, NFSv3, NFSv4, NFSv4.1, NFS Kerberized sessions, iSCSI, HTTP, HTTPS, FTP, SNMP, LDAP,
---------------------	---



## CalDAV

- Chrome
- Firefox
- Edge
- Safari

## Supported Browsers

## Supported Language

English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svenska, Nederlands, ???????, Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, ?eský, ???????, ???, ???, ????, ????

## Notes

For an updated list of supported browser versions, check the [DSM Technical Specifications](#).

Add-on Packages [view the complete package list](#)  
[Central Management System](#)  
[Synology Chat](#)

## Suggested Users Notes

100

- Measured with simulated users, each with an average record of 20,000 messages, emojis, or stickers. The required server response time is below ten seconds.
- Models with expandable memory are tested with their maximum supported memory.

## Download Station

## Maximum Concurrent Download Tasks

80

## [SAN Manager](#)

## Maximum iSCSI Target Number

128

## Maximum LUN LUN Clone/Snapshot, Windows ODX

256

## [Synology MailPlus / MailPlus Server](#)

## Free Email Accounts

5 ([Additional accounts  
require purchase of licenses](#))

Suggested Users  
Maximum Server  
Performance  
Notes

500  
1,224,000 emails per day,  
approx. 37GB

- Suggested users is derived from testing in an environment with 20% heavy users (each with 20,000 pre-populated emails and receiving 240 emails per day) and 80% light users (each receiving an average of 20 emails per day). [Learn more](#)
- Models with more than 4 bays were installed with two SSDs for SSD cache.
- Models with expandable memory are tested with their maximum supported memory.
- The performance of the mail system will slightly decrease in high-availability mode due to data synchronization between the two servers.
- Functions that were enabled in all of the tests above: anti-spam, anti-virus, DNSBL, greylist, content scan, full-text search (English only).

[Media Server](#)  
[Synology Photos](#)

DLNA Compliance  
Facial Recognition  
Object Recognition

## Snapshot Replication

Maximum Snapshots per Shared Folder 1,024

Maximum of System Snapshots 65,536

## Surveillance Station

Default Licenses 2 [\(Additional cameras require purchase of licenses\)](#)

Suggested Maximum IP Cameras and Total FPS (H.264)

- 720p: 40 channels, 1200 FPS
- 1080p: 40 channels, 1050 FPS
- 3M: 40 channels, 600 FPS
- 5M: 30 channels, 360 FPS
- 4K: 20 channels, 200 FPS

Suggested Maximum IP Cameras and Total FPS (H.265)

- 720p: 40 channels, 1200 FPS
- 1080p: 40 channels, 1200 FPS
- 3M: 40 channels, 1000 FPS
- 5M: 40 channels, 600 FPS
- 4K: 30 channels, 300 FPS

Notes

- Performance figures are obtained from testing conducted with the device fully populated with drives, with their default memory configuration, and under a continuous recording setup. Actual system capabilities may vary based on configuration, drive performance, enabled features, and the

presence of additional workloads.

- Use [NVR Selector](#) to quickly find a suitable model based on your requirements.
- The maximum number of camera stream outputs is 2 times the suggested maximum number of IP cameras.

## [Synology Drive](#)

Recommended Number of Concurrent Sync Clients

350 (the number of connections that can be maintained when the recommended number of hosted files was reached)

Recommended Number of Hosted Files

5,000,000 (applies to files indexed or hosted by [Synology Drive](#). For file access through other standard protocols, refer to the File Services section above)

Notes

- Exceeding the recommended numbers above will not block application operations, but may result in longer response time.
- Utilizing SSD cache can significantly improve performance.
- Models with expandable memory are tested with their maximum supported memory.
- Btrfs file system and non-encrypted shared folders were used during the

## [Synology Office](#)

Suggested Users  
Notes

3,000

aforementioned  
testing.

- Suggested users is derived from testing in an environment with 60% idle users (each logging in and viewing documents) and 40% active users (each executing random actions at intervals of 20 to 40 seconds) operating within documents, each document having 30 users. [Learn more](#)
- Models with expandable memory are tested with their maximum supported memory.
- Client performance may affect maximum simultaneous editing users. Client PCs used for testing: Intel Core i3-3220 / 8GB RAM

## [Virtual Machine Manager](#)

Recommended Virtual  
Machine Instances

4 [\(Learn more\)](#)

Recommended Virtual DSM  
Number [\(Licenses required\)](#)

4 (including 1 Free License)

Notes

The specifications vary  
depending on system  
configuration and memory  
size.

## [VPN Server](#)

Maximum Connections

40

## Specification

NAS	
CPU Model	AMD Ryzen R1600
CPU Quantity	1

CPU Core	2
CPU Architecture	64-bit
CPU Frequency	2.6 (base) / 3.1 (turbo) GHz
Hardware Encryption Engine	YES
Memory	8 GB DDR4 ECC SODIMM
Drive Bays	5
Compatible Drive Type	3.5
Hot Swappable Drive	YES
RJ-45 1GbE LAN Port	4
RJ-45 1GbE LAN Port	2
System Fan	92 mm x 92 mm x 2 pcs
Power Supply Unit / Adapter	120 watts 100V to 240V AC 50/60 Hz, Single Phase
Total Memory Slots	2
Maximum Memory Capacity	64 GB (32 GB x 2)
M.2 Drive Slots	2 (NVMe)
Expansion Port	2
PCIe Expansion	1 x Gen3 x2 network upgrade slot

## Product Gallery



